

TECHNICAL DATA SHEET NO:MAMSPRAY05 VERSION: 1
PAGE: 1 OF 2 DATE OF ISSUE: 2/23/2015

#### **EVERBUILD MAMMOTH SPRAY ADHESIVE**



Colour	<b>Product Code</b>	Pack Size	<b>Box Qty</b>
AMBER	2SPRAY05	500ml	12

### **Product Description**

MAMMOTH SPRAY ADHESIVE is sprayable medium duty glue which fixes P.U and foam backed carpets, carpet tiles, underlay, paper felt and cork to most common substrates.

#### **Benefits**

- Good adhesion fast rate of tack development.
- Ease of use no messy spreading/clean up
- Time saving- easier and quicker than most trowel/spreader applied adhesives.
- Foaming formula gives low soak in into most substrates.
- Halogen and CFC Free.
- Repositionable.

## Uses

- Fixing most common types of PU and foam backed carpets to most common surfaces.
- Fixing carpet tiles.
- · Bonding metals to most surfaces.
- Bonds rubber, most plastics and leather
- As a general purpose household/hobby adhesive

# **Application**

Shake the can well before use.

The surfaces to be glued should be clean and free from dust, grease and other contaminants. Materials should be stored in a warm environment prior to bonding to avoid chilling of the glue line, which leads to extended setting times.

Select the fan width by turning the nozzle to the desired position. Spray adhesive from 6-8 inches away onto one or both surfaces; depending on the type of surface/strength of bond required. The surfaces to be glued should be clean and free from dust, grease and other contaminants. Shake well before use. Select fan width by turning to desired setting. Spray adhesive from 6 to 8 inches (15 to 20 cms approx.) away onto one or both surfaces, depending on type of strength of bond required.

## STRONG BONDING

Apply 1-3 coats (depending on strength required) to both surfaces. Allow solvent to evaporate (30 seconds) and press surfaces together from centre outwards.

## **TEMPORARY REPOSITIONABLE BONDING:**

Spray on one surface only and allow to dry for 2-3 minutes before bonding. Excess adhesive can be removed with STICK 2 CONTACT ADHESIVE THINNER AND CLEANER. To prevent spray nozzle from



**VERSION: 1** 

TECHNICAL DATA SHEET NO:MAMSPRAY05

PAGE: 2 OF 2 DATE OF ISSUE: 2/23/2015

blocking, at the end of each day, turn can upside down and press nozzle until spray is clear of adhesive.

Excess adhesive can be removed using EVERBUILD GUN FOAM CLEANER. To prevent spray nozzle from blocking,; at the end of each use, turn can upside down and press nozzle until spray is clear of adhesive.

The newly bonded materials should not be subjected to extreme temperature changes for 3 to 4 days after bonding. Avoid further fabrication until the adhesive has fully cured.

### **Specific Data**

Colour	Yellow/Amber	
Base	Synthetic rubber/resin	
Solids	10 – 20%	
Viscosity	Low	
Coverage	120 – 250m²	
Tack Life	2 – 5 mins	
Flash Point	-40°C	
Cleaner	Everbuild Gun Foam Cleaner	

### **Health & Safety**

Consult MSDS for full list of hazards.

### **Storage**

Store in original unopened containers between 5 and 25°C. Store as flammable liquid.

# **Shelf Life**

Shelf life 36 months from date of manufacture

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.