

R200 SPOT REPAIR

Page: 1

Compilation date: 12.09.2012

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: R200 SPOT REPAIR

Product code: BONA165

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Spot repair

1.3. Details of the supplier of the safety data sheet

Company name: Bona GmbH

Jahnstraße 12

D - 65549 Limburg

Deutschland

Tel: +49-6431-4008-0 **Fax:** +49-6431-4008-25

Email: empfang@bona.com

1.4. Emergency telephone number

Emergency tel: +49-761-19240

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20

Classification under CLP: Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit.

2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 2: H371; -: EUH204

Most important adverse effects: Harmful by inhalation. Irritating to eyes, respiratory system and skin. Limited

evidence of a carcinogenic effect. May cause sensitisation by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged exposure

through inhalation.

2.2. Label elements

Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H371: May cause damage to organs . H351: Suspected of causing cancer.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

R200 SPOT REPAIR

Page: 2

H373: May cause damage to organs through prolonged or repeated exposure.

EUH204: Contains isocyanates. May produce an allergic reaction.

Signal words: Danger

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard





Precautionary statements: P260: Do not breathe.

P280: Wear.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at

rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical.

Label elements under CHIP:

Hazard symbols: Harmful.



Risk phrases: R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitisation by inhalation and skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure

through inhalation.

Safety phrases: S23: Do not breathe vapour.

S36/37: Wear suitable protective clothing and gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

R200 SPOT REPAIR

Page: 3

3.2. Mixtures

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent	
202-966-0	101-68-8	Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20	Carc. 2: H351; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317; STOT SE 2: H371; STOT RE 2: H373	30-50%	
AROMATISCH	ES POLYISOCY	ANAT-PREPOLYMER.			
-	67815-87-6	Sens.: R42/43	Skin Sens. 1: H317; Resp. Sens. 1: H334	10-30%	
DIPHENYLME ⁻	THANE-2,4'-DI-IS	SOCYANATE			
227-534-9	5873-54-1	Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20	Carc. 2: H351; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317; STOT SE 2: H371; STOT RE 2: H373	10-30%	
AROMATISCH	ES POLYISOCY	ANAT-PREPOLYMER			
-	72088-97-2	Sens.: R42/43	Resp. Sens. 1: H334; Skin Sens. 1: H317	10-30%	
DIPHENYLME ⁻	THANE-2,2'-DI-IS	SOCYANATE			
219-799-4	2536-05-2	Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20	Carc. 2: H351; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317; STOT SE 2: H371; STOT RE 2: H373	1-10%	
DIPHENYLME ⁻	THANE DIISOCY	ANATE (ISOMERS AND HOMOLOGU	ES)		
-	9016-87-9	Xn: R20; Xi: R36/37/38; Xn: R40; Sens.: R42/43; Xn: R48/20	Carc. 2: H351; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317; STOT SE 2: H371; STOT RE 2: H373	1-10%	

Contains: Mixture of synthetich resin, mineralic fillers and additives

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult

a doctor. [cont...]

R200 SPOT REPAIR

Page: 4

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure

may cause coughing or wheezing.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No data available.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water

spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach

from downwind. If outside keep bystanders upwind and away from danger point.

Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

porconition runnicalising containers real election up to prove

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the

area. Do not handle in a confined space. Avoid the formation or spread of mists in

the air.

R200 SPOT REPAIR

Page: 5

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m3	0.07 mg/m3	-	-

DIPHENYLMETHANE-2,4'-DI-ISOCYANATE

UK	0.02 mg/m3	0.07 mg/m3	-	-	
----	------------	------------	---	---	--

DIPHENYLMETHANE-2,2'-DI-ISOCYANATE

UK	0.02 mg/m3	0.07 mg/m3	_	_
OIX	0.02 1119/1110	0.07 1119/1110		

DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

UK 0.02 mg/m3 0.07 mg/m3 -

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Brown
Odour: Aromatic

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Reacts with water.

Also soluble in: Most organic solvents.

Kinematic viscosity: 220 mPa*s

Boiling point/range°C: > 350 Melting point/range°C: < 0

Flash point°C: > 210

R200 SPOT REPAIR

Page: 6

Autoflammability°C: > 400

Vapour pressure: <10e-5 mbar Relative density: 1,17

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No data available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: Not applicable.

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure

may cause coughing or wheezing.

Delayed / immediate effects: No data available.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

R200 SPOT REPAIR

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the

mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU)

No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH204: Contains isocyanates. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

R200 SPOT REPAIR

Page: 8

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R42/43: May cause sensitisation by inhalation and skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.