



SAFETY DATA SHEET

DATE PREPARED/REVISED. 09/02/06

Supersedes SDS dated

Issue Date. 13/11/2008

1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY:

PRODUCT NAME: CLICSEAL
SUPPLIER: UNIKA COLOR PRODUCTS LTD.
NEW YORK INDUSTRIAL PARK,
NEWCASTLE UPON TYNE, NE27 0QF

TELEPHONE: +44 (0) 191 259 0033

2. COMPOSITION/INFORMATION ON INGREDIENTS:

Adhesive, containing solvent

INGREDIENT NAME	CAS No EINECS No	CONTENTS in %	HEALTH	RISK
Naphtha	64742-49-0 265-151-9	50 - 100 %	F,Xn,N	11,51/53,65,38,67
Cyclohexane	110-82-7 2.5 203-806-2	10 %	F,N,Xn	11,38,50/53,65,67

3. HAZARDS IDENTIFICATION:

Highly flammable.
Irritating to skin.
Vapours may cause drowsiness and dizziness
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES:

EYES: In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Summon a doctor immediately.

SKIN: In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.

INHALATION: In the event of symptoms take medical treatment.

INGESTION: Do not induce vomiting. Summon a doctor immediately.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA	Dry powder, carbon dioxide or foam. Full water jet is unsuitable
SPECIAL FIRE FIGHTING PROCEDURES	Use breathing apparatus.
UNUSUAL HAZARDS	Fire residues and contaminated firefighting medium must be disposed of in accordance with the local regulations. Collected contaminated firefighting water must not be discharged into the drains.

6. ACCIDENTAL RELEASE MEASURES:

PERSONAL PROTECTION	Ensure adequate ventilation. Use personal protective clothing and breathing apparatus if exposed to vapours/dust/aerosol.
ENVIRONMENTAL PRECAUTIONS	Do not allow to enter drains or waterways. If entry into waterways, soil or drains happened then inform the responsible authorities.
SPILL CLEANUP METHODS	Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder) then treat material as prescribed in Section 13 "Disposal".

7. HANDLING AND STORAGE:

HANDLING	See Chapter 8 Personal Protection. Keep away from sources of ignition - no smoking. Vapours may form explosive mixtures with air Take precautionary measures against electrostatic discharge.
STORAGE	Keep container tightly closed in a cool dry, well-ventilated place Protect from frost, heat and direct sunlight

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT	CAS No.	STEL	LTEL (8hrs)
Cyclohexane	110-82-7	350 mg/m3	
VENTILATION	Ensure sufficient ventilation or exhaust in the workshop place		
PERSONAL PROTECTION	Avoid contact with eyes and skin-Use Safety glasses and barrier skin cream. Remove soiled or soaked clothing immediately. Do not eat, drink or smoke - Wash hands before breaks and after work.		

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance	Liquid
Odour	characteristic
Colour	Transparent
Specific Gravity	0.75
VOC (Solvent)	91%
VOC (CH)	91 %
Flash point	-18°C
Viscosity	40nPas

10. STABILITY AND REACTIVITY:

CONDITIONS TO AVOID	Formation of explosive gas/air mixtures.
MATERIALS TO AVOID	No hazardous reactions when stored and handled according to prescribed instructions.
HAZARDOUS DECOMPOSITION PRODUCTS	No decomposition if used as prescribed.

11. TOXICOLOGICAL INFORMATION:

HEALTH WARNINGS	Repeated exposure may cause skin dryness or cracking May cause eye irritation. Vapours have a narcotic effect. Reaction time and coordination may be affected. When swallowed, small amount may cause considerable health disorders.
-----------------	---

12. ECOLOGICAL INFORMATION:

ECOTOXICITY	Do not allow to enter waste water drain, waterways or soil.
-------------	---

13. DISPOSAL CONSIDERATIONS:

Must be disposed of in a special waste disposal unit in accordance with the corresponding regulations. Completely empty packaging may be given for recycling but may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

14. TRANSPORT INFORMATION:

1. Classification

UN Number	1133
CLASS	3
Class code	F1
PACKING	II
PROPER SHIPPING NAME	Adhesive
EMS	F-E, S-D
MARINE POLLUTANT	No


15. REGULATORY INFORMATION:

LABEL FOR SUPPLY


According to EC-Directives 67/548/EEC on 1999/45/EC



Highly
Flammable



Harmful



Dangerous for the environment

RISK PHRASES

R11	Highly flammable
38	Irritating to skin
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
67	Vapours may cause drowsiness and dizziness

SAFETY PHRASES

S (02)	Keep out of reach of children
23	Do not breath vapour
33	Take precautionary measures against static discharges
51	Use only in well-ventilated areas

16. OTHER INFORMATION:

*The information contained in this Data Sheet is provided in accordance with the **Chemicals (Hazard Information and Packaging for Supply) Regulations 2002** for the purpose of protecting the health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided. This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with legal regulations. The information contained herein is based on the current state of our knowledge and is intended to describe products from the point of view of safety requirements and thus should not be construed as guaranteeing specific properties.*

Please ensure that it is passed to the appropriate person(s) in your company, who are capable of acting on the information.