

Colorsealant



- ColorSealant can be over painted and lacquered when dry.

Directions for Use:

Ensure surfaces are clean and dry.

Apply bead of ColorSealant to gap. Use finger to smooth into shape.

Clean up with a clean damp cloth.

Consumer Benefits:

ColorSealant is available in a wide range of wood colours.

ColorSealant can be over painted and lacquered when dry.

ColorSealant is ideal for filling gaps between flooring and walls or skirting boards and acts as an expansion mechanism allowing the floor to expand and contract.

ColorSealant is also ideal for filling general gaps where flooring planks are cut to fit around difficult obstacles such as fireplaces, doorways etc.

Retailer Opportunity:

ColorSealant is available in a wide range of wood colours and special colours can be manufactured depending on minimum order quantities.

ColorSealant is available in a 310ml cartridge with a colour coded nozzle.

ColorSealant is a brand name and has been tried and tested in the market for the last 15 years.

ColorSealant merchandising counter tray is available with a stock order.

ColorSealant is a waterbased product which means it is friendly to the environment.

Product Description:

ColorSealant – Acrylic gap filler for laminate and timber flooring.

Key Features:

- ColorSealant is a waterbased acrylic gap filler designed specifically for the installation of laminate and solid wood flooring.
- ColorSealant is water clean up.
- ColorSealant is available in a wide range of colours designed to match the most popular laminate and woodgrain finishes.
- ColorSealant is waterproof once fully cured.
- ColorSealant is flexible and will not crack, it will expand and contract with the floor.

UNIKA COLOR PRODUCTS LTD

Unika House, New York Way, New York Industrial Park, Newcastle upon Tyne, U.K. NE27 0QF

Telephone: +44 (0) 191 259 0033

Fax: +44 (0) 191 257 4525

Email: sales@unika.co.uk www.unika.co.uk

