

THERMOFOAM

Colour	Product Code	Pack Size	Box Qty
Beige	EVTHERM7	750ML	12

Product Description

Everbuild Thermofoam is a specially formulated, highly flexible PU foam that absorbs component movement thereby giving an air tight seal to reduce heat loss and improve energy efficiency in buildings.

The powerful bond strength and flexibility of Thermofoam gives excellent long term thermal and acoustic insulation by inhibiting cracks from occurring during the contraction of building materials, such as window frame to wall bonds, giving a hermetically sealed barrier.

Benefits

- Adheres to all common building materials including concrete, brickwork, wood, plaster, plastic, stone, metal etc.
- Acoustic insulation up to 64 dB (EN ISO 717-1)
- Certified Air permeability: $a < 0,1 \text{ m}^3$ to EN 12114:200-03
- Temperature Resistant -40 to +80°C (short term exposure to +100°C)
- Fire Rated to ISO13501 (Class E)

Areas for Use

- Window installation (clean, controlled back filling and insulated sealing of window and external roller blind cavities)
- Gap filling of external door frames (must be used in conjunction with mechanical fixings)
- Filling cavities in wall break-through for all types of utilities and services.

Limitations

- Carefully read instructions and text in warning box before use.
- For Professional use only.
- Do not over pressurize container.
- Always apply above 5°C.
- Clean spills immediately with EVERFLEX FOAM CLEANER.
- Always clean the gun thoroughly with EVERFLEX FOAM CLEANER until the jet is clear of foam. Leave the canister attached until the gun is to be used again
- It is the user's responsibility to determine suitability for use. If in doubt contact Everbuild Technical Services for advice.

Surface Preparation

Ensure all surfaces are clean, sound and free from dust and loose particles. **Moisten surfaces to be sealed with water. This assists the curing process.**

Application

- Carefully read instructions before use.
- Ensure all surfaces are clean, sound and free from dust and loose particles. Remove loose particles and moisten surfaces with water immediately prior to application. All components should be prepared ready for bonding.
- Moisten surfaces to be sealed with water - this assists the curing process. Shake can well before use and before attaching to the gun. Remove black cap and screw gun carefully onto the black adapter of the can. Take care not to over tighten.
- ALWAYS USE WITH CAN UPSIDE DOWN.
- The trigger should be depressed gently to control the foam release. Moistened released foam evenly. In large cavities moistening layer-by-layer is recommended. Inadequate wetting and overfilling cavities can cause undesirable subsequent foam expansion. Foam expands by around 30%
- Once cured, foam can be removed with a knife or scraper. The gun can be left attached to the can in between jobs. When the gun is removed for storage, ALWAYS thoroughly purge with Everbuild Foam Cleaner. All information on the Technical Data Sheets for the application of gun foam and applicator guns must be observed.

Please note:

When transported in cars, keep in boot, out of direct sunlight.

When removing cured foam from skin, take care not to damage with abrasives.

Grease skin with body lotion or similar.

IMPORTANT – Re-use is only possible by cleaning the nozzle and valve tip with EVERBUILD DUAL PURPOSE FOAM CLEANER before the foam has cured. Do not push any object into the valve as the contents may explode.

Specific Data

Expansion	Up to 41 litres (output under free release of a 750ml canister)
Cell Structure	Fine
Tack Free	Approx. 7-10mins
Cutttable	10-13 mins (20mm bead, moist application)
Full Load Bearing Stability	Approx. 24 hours (20mm bead)
Working Temps	+10°C - +30°C. (Optimum 20°C)
Elongation at break	23-28%
Compressive strength @10% stress	Approx. 1kg/M ²
Absorption of water	0.3% Vol-%
Material Classification (EN13501)	Class E
Certified sound insulation	Max. 64dB
Air tightness	<0.1 M ³ /H
Temp Res Of Cured Bead	Long Term: -40 - +80°C Short Term: -40 - +100°C
Building Material Class	B3 (DIN 4102, Part 1)

Health & Safety

Consult MSDS for full list of hazards

Storage

Store upright between 10 and 20°C Pressurized container. Protect from sunlight and do not expose to temperatures above 50°C. Do not pierce or burn the can even after use. Store as flammable liquid.

Note: Elevated temperatures will reduce shelf life dramatically. Protect from heat and frost.

Shelf Life

12 months in original containers at stated storage temperatures.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.