

METHYLATED SPIRITS

Page: 1

Compilation date: 17/6/13

**Revision No:** 3

### Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: METHYLATED SPIRITS

Product code: MS5

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

**LEEDS** 

WEST YORKSHIRE

LS9OSW ENGLAND

**Tel:** 0044 113 240 3456 **Fax:** 0044 113 240 0024

Email: pault@everbuild.co.uk

### 1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

### **Section 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225

Classification under CHIP: F: R11

Most important adverse effects: Highly flammable liquid and vapour.

## 2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

Signal words: Danger

Hazard pictograms: GHS02: Flame



Precautionary statements: P101: If medical advice is needed, have product container or label at hand.

P242: Use only non-sparking tools.
P102: Keep out of reach of children.

#### **METHYLATED SPIRITS**

Page: 2

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water/shower.

P280: Wear eye protection.

P103: Read label before use.

P233: Keep container tightly closed.

P403+235: Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### **Hazardous ingredients:**

### **ETHANOL**

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	70-90%
PROPAN-2-OL				
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	1-10%
ETHYL METHY	L KETONE			

# Section 4: First aid measures

201-159-0

### 4.1. Description of first aid measures

78-93-3

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

Flam. Liq. 2: H225; Eye Irrit. 2: H319;

STOT SE 3: H336; -: EUH066

on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

1-10%

#### METHYLATED SPIRITS

Page: 3

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

### 4.3. Indication of any immediate medical attention and special treatment needed

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool

containers.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

## 6.4. Reference to other sections

### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

#### METHYLATED SPIRITS

Page: 4

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

### Hazardous ingredients:

#### **ETHANOL**

### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	-

#### **PROPAN-2-OL**

		UK	999 mg/m3	1250 mg/m3	-	
--	--	----	-----------	------------	---	--

### **ETHYL METHYL KETONE**

UK	600 mg/m3	899 mg/m3	_	_

### 8.1. DNEL/PNEC Values

#### DNEL / PNEC No data available.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). and must be worn if vapour

concentration exceeds WEL

Hand protection: Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Purple

Odour: Sweet-smelling

**Evaporation rate:** Fast **Solubility in water:** Soluble

Also soluble in: Most organic solvents.

METHYLATED SPIRITS

Page: 5

Viscosity: Non-viscous

Flammability limits %: lower: 3.5 upper: 19

Flash point°C: 13 Autoflammability°C: 400

Vapour pressure: 5.81 kPa 20 Relative density: 0.8-0.85

VOC g/I: 825

### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

### 11.1. Information on toxicological effects

## Hazardous ingredients:

#### **ETHANOL**

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

Toxicity values: No data available.

#### METHYLATED SPIRITS

Page: 6

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

### **Section 12: Ecological information**

### 12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: Extra data available on raw material components

### 12.3. Bioaccumulative potential

Bioaccumulative potential: Extra data on raw materials available

### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

## 12.6. Other adverse effects

Other adverse effects: Extra data on raw materials available

## Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste code number: 070104

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

### **Section 14: Transport information**

### 14.1. UN number

UN number: UN1170

## 14.2. UN proper shipping name

Shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

### 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: ||

#### METHYLATED SPIRITS

Page: 7

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

### Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### **Section 16: Other information**

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

R11: Highly flammable.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.