

TimberTech Elite Plus Underlay

Premium acoustic underlay with outstanding noise reduction

Shhh! Underlay at work

TimberTech Elite Plus reduces walking noise by up to 32% and impact sound by up to 21dB, which really cuts down the noise level in the room and makes it a more comfortable place to be.

■ Underfloor heating underlay

Elite Plus has a very low tog value of 0.1, making it the perfect choice if you have underfloor heating, letting it heat the floor more efficiently.

■ The strength from underneath

The high density and compressive strength fully supports the floor and prevents movement, keeping it in good shape for a longer life.

Protects against moisture

Silver vapour barrier gives superior protection against moisture rising up from the sub-floor, keeping your floor dry.

Technical Data		
Properties	Value	Method
Thickness	3mm ±0.3mm	
Roll Size	$1m \times 10m = 10m^2$	
Roll Weight	24kg ±10%	
Density	850 kg/m3 ±10%	
Walking Sound Reduction/ Reflected Walking Sound (RWS)	Up to 32% ± 2%	EPLF WD 021029-5
Impact Sound Reduction	21dB ± 2dB	DIN EN 16251-1
Thermal Resistance	0.1 tog	DIN CEN/TS 16354
Compressive Strength	Up to 120 kPa	DIN EN 826
Compressive Creep	~ 29 kPa	DIN CEN/TS 16354
Dynamic load	> 2,000,000 cycles	DIN CEN/TS 16354
Resistance to large ball	~ 800 mm	DIN CEN/TS 16354
Punctual conformability	~ 1.55 mm	DIN CEN/TS 16354
Reaction to fire	Bfl-s1	DIN EN 13501-1
Formaldehyde Content	0	
VOC's	A+	

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive Liverpool, L24 8RL Tel: 0151 495 3434 Fax: 0151 427 0484

Email: sales@qaflooringsolutions.com www.gaflooringsolutions.com

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

Simply Better

Heavy **Traffic**

Wood



Best for

Moisture **Protection**

Sound Reduction

Floors

Recovery

Underfloor Heating

Wearing

*Suitable for hotels and public buildings

Available in

Code QAU-TTE-02 Size 1m x 10m (10m²) Thickness 3mm