

- High Performance Oil system
- The complete solution for high traffic floors
- Fast drying and easy application
- Enhances the natural beauty of wooden flooring
- Luxurious finish
- Water resistant

#### How Does It Work?

Treating a newly sanded floor with Junckers HP Oil gives it a beautiful finish and emphasises the natural warmth and lustre of the wood. It penetrates the wood deeply and so is exceptionally water and stain resistant, it won't crack or peel and allows the wood to "breathe" naturally.

Periodically maintain the floor with Junckers HP Oil Recoat, which maintains the high level of protection offered by HP Oil. HP Oil Recoat is very quick and easy to apply, and fast drying. Also you don't have to treat the whole floor area if you don't need to- so "down- time" is kept to an absolute minimum.

Daily cleaning is easy with Junckers Floor Oil Cleaner. This is an effective cleaning solution specially developed to be part of the HP Oil system. It is quick and easy to use and so if needed, may be used every day. It leaves no residue behind, keeps the floor looking beautiful, and makes sure that the HP Oil keeps on protecting the wood.







## FOR PRIMING AND FINISHING OF NEWLY SANDED WOODEN FLOORS

Junckers HP Oil brings out the warm natural colours in the wood and protect is from wear and tear, stains and scuffs.

If you like the oiled look but prefer to maintain it like a lacquered floor then- use HP Oil in combination with Junckers HP Commercial lacquer.

**Procedure:** Prepare the floor and apply the first coat of oil. On the following day apply the finishing coat. Ready for use the following day.



### **Can size:** 0,75 + 2,5 litre



## FAST DRYING AND EASY TO USE. A MAINTENANCE AND REFRESHING OIL FOR WOODEN FLOORS PRE-TREATED WITH JUNCKERS HP OIL.

Specially formulated for maintaining floors which have been treated with Junckers HP Oil – Just make sure that the floor is absolutely clean before use.

Junckers HP Oil Recoat can be used to "spot repair" the finish, so you don't have to treat the whole floor area

**Procedure:** Clean and abrade the floor and apply HP OIL Recoat with a cloth or buffing maching. Ready for light traffic after 3 to 4 hours.



#### Can size:

0.75 + 2.5 litre



# THE ULTIMATE DEEP CLEANER FOR REGULAR CLEANING OF FLOORS TREATED WITH HP OIL AND HP OIL RECOAT.

Specially developed for use with the Junckers HP Oil system.

**Procedure:** Dilute with warm water and use it whenever a quick drying cleaning is required. Use daily, weekly or as required.




### Can size:

1 + 5 litre

#### More information

For additional information, refer to the technical data sheets, Junckers HP Oil F 20.1, Junckers HP Oil Recoat F 20.2, Junckers Floor Oil Cleaner F. 10.7 and the material Safety Data Sheet for detailed information about precautionary measures.



every time.